


**Socket Head Cap Screws with Pilot Recess, (Low Type)**

Tornillos allen cabeza baja

Vis à tête cylindrique à six pans creux avec tête basse et trou de guidage

A2
A4



d1	M4	M5	M6	M8	M10	M12	M16	M20	M24
d2	7	8.5	10	13	16	18	24	30	36
b	14	16	18	22	26	30	38	46	
k	2.8	3.5	4	5	6.5	7.5	10	12	14
e	3.6	4.7	5.9	7	9.4	11.7	16.3	19.8	22.1
s	3	4	5	6	8	10	14	17	19
pitch	0.7	0.8	1	1.25	1.5	1.75	2	2.5	3

d	L	W
M4	10	1.30
M4	12	1.50
M4	16	1.90
M4	20	2.30
M4	25	2.70
M4	30	3.20
M4	35	3.40
M4	40	4.20
M5	10	2.20
M5	12	2.50
M5	16	3.10
M5	20	3.70
M5	25	4.40
M5	30	5.10
M5	35	5.80
M5	40	6.60
M5	45	7.40
M6	10	3.60
M6	12	3.90
M6	16	4.50
M6	20	5.20
M6	25	6.20
M6	30	7.30
M6	35	8.30
M6	40	9.50
M6	45	10.5

d	L	W
M 6	50	11.5
M 6	55	12.6
M 6	60	13.6
M 6	70	15.7
M 8	10	7.15
M 8	12	7.70
M 8	16	8.80
M 8	20	10.2
M 8	25	12.5
M 8	30	14.0
M 8	35	15.7
M 8	40	17.5
M 8	45	19.5
M 8	50	21.5
M 8	55	23.4
M 8	60	25.3
M 8	70	29.1
M 8	80	32.8
M 8	90	36.5
M 8	100	40.2
M10	16	15.5
M10	20	17.9
M10	25	20.2
M10	30	22.0
M10	35	25.5
M10	40	28.5

d	L	W
M10	45	31.6
M10	50	34.8
M10	55	37.6
M10	60	40.3
M10	70	46.0
M10	80	52.5
M10	90	57.8
M10	100	63.1
M12	16	22.3
M12	20	25.5
M12	25	29.5
M12	30	32.5
M12	35	36.5
M12	40	40.0
M12	45	44.0
M12	50	48.0
M12	55	52.5
M12	60	57.0
M12	70	65.0
M12	80	72.0
M12	90	80.0
M12	100	88.0
M16	25	56.5
M16	30	63.0
M16	35	69.7
M16	40	78.7

d	L	W
M16	45	85.1
M16	50	91.5
M16	55	99.2
M16	60	107
M16	70	122
M16	80	140
M16	90	154
M16	100	169
M16	110	183
M16	120	198
M16	130	212
M16	140	226
M16	150	240
M20	40	128
M20	45	139
M20	50	150
M20	55	161
M20	60	172
M20	70	196
M20	80	222
M20	90	245
M20	100	269
M20	110	292
M20	120	316
M20	130	342
M20	140	368

d	L	W
M20	150	394
M24	55	247
M24	60	263
M24	70	298
M24	80	333
M24	90	369
M24	100	407
M24	110	439
M24	120	474
M24	130	510
M24	140	545
M24	150	580

(W ~ Weights of standard sizes in kilograms per 1000 pieces)