


Slotted Pan Head Tapping Screws

Pijas cabeza fijadora ranurada

Vis à tôle à tête cylindrique avec fente

A2
A4



d	2.2	2.9	3.5	3.9	4.2	4.8	5.5	6.3
d (U.S. equiv)	#2	#4	#6	#7	#8	#10	#12	1/4
d ₂	4.2	5.6	6.9	7.5	8.2	9.5	10.8	12.5
k max.	1.35	1.75	2.1	2.25	2.45	2.8	3.2	3.65
k min.	1.15	1.5	1.85	2	2.15	2.5	2.85	3.3
n	0.6	0.8	1	1	1.2	1.2	1.6	1.6

d	L	W
2.2	6.5	.210
2.2	9.5	.274
2.2	13	.344
2.2	16	.404
2.2	19	.464
2.2	22	.524
2.2	25	.584
2.9	6.5	.424
2.9	9.5	.532
2.9	13	.658
2.9	16	.766
2.9	19	.874
2.9	22	.982
2.9	25	1.09
3.5	6.5	.690
3.5	9.5	.840
3.5	13	1.02
3.5	16	1.17
3.5	19	1.32
3.5	22	1.47
3.5	25	1.62
3.5	32	1.77
3.5	38	2.07
3.9	9.5	1.07
3.9	13	1.29
3.9	16	1.48

d	L	W
3.9	19	1.67
3.9	22	1.86
3.9	25	2.05
3.9	32	2.49
3.9	38	2.87
3.9	45	3.31
3.9	50	3.62
3.9	60	4.25
4.2	9.5	1.26
4.2	13	1.50
4.2	16	1.71
4.2	19	1.92
4.2	22	2.13
4.2	25	2.34
4.2	32	2.83
4.2	38	3.25
4.2	45	3.74
4.2	50	4.09
4.2	60	4.79
4.2	70	5.49
4.2	80	6.19
4.8	9.5	1.85
4.8	13	2.20
4.8	16	2.50
4.8	19	2.80
4.8	22	3.10

d	L	W
4.8	25	3.40
4.8	32	4.10
4.8	38	4.70
4.8	45	5.40
4.8	50	5.90
4.8	60	6.90
4.8	70	7.90
4.8	80	8.90
4.8	90	9.90
4.8	100	10.9
5.5	13	2.95
5.5	16	3.34
5.5	19	3.73
5.5	22	4.12
5.5	25	4.51
5.5	32	5.42
5.5	38	6.20
5.5	45	7.11
5.5	50	7.76
5.5	60	9.06
5.5	70	10.4
5.5	80	11.7
5.5	90	13.0
5.5	100	14.3
6.3	13	4.32
6.3	16	4.86

d	L	W
6.3	19	5.40
6.3	22	5.94
6.3	25	6.48
6.3	32	7.74
6.3	38	8.82
6.3	45	10.1
6.3	50	11.0
6.3	60	12.8
6.3	70	14.6
6.3	80	16.4
6.3	90	18.2
6.3	100	20.0

(W ~ Weights of standard sizes in kilograms per 1000 pieces)