


Phillips Cross Recessed Pan Head Tapping Screws

Pijas cabeza pan de estrella

Vis à tôle à tête cylindrique avec empreinte cruciforme

A2
A4

Type C



d	2.2	2.9	3.5	3.9	4.2	4.8	5.5	6.3
d (U.S. equiv)	#2	#4	#6	#7	#8	#10	#12	1/4
d ₂	4.2	5.6	6.9	7.5	8.2	9.5	10.8	12.5
k max.	1.8	2.2	2.6	2.8	3.05	3.55	3.95	4.55
k min.	1.55	1.95	2.35	2.55	2.75	3.25	3.65	4.25
m	2.6	3	4.2	4.4	4.6	5	6.5	7.1

d	L	W
2.2	6.5	.200
2.2	9.5	.260
2.2	13	.330
2.2	16	.390
2.2	19	.450
2.2	22	.510
2.2	25	.570
2.9	6.5	.400
2.9	9.5	.510
2.9	13	.630
2.9	16	.740
2.9	19	.850
2.9	22	.960
2.9	25	1.07
3.5	6.5	.640
3.5	9.5	.790
3.5	13	.970
3.5	16	1.12
3.5	19	1.27
3.5	22	1.42
3.5	25	1.57
3.5	32	1.92
3.5	38	2.22
3.5	45	2.57
3.5	50	2.82
3.9	9.5	1.05

d	L	W
3.9	13	1.27
3.9	16	1.46
3.9	19	1.65
3.9	22	1.84
3.9	25	2.03
3.9	32	2.47
3.9	38	2.85
3.9	45	3.30
3.9	50	3.61
3.9	60	4.25
4.2	9.5	1.22
4.2	13	1.46
4.2	16	1.67
4.2	19	1.88
4.2	22	2.10
4.2	25	2.30
4.2	32	2.80
4.2	38	3.23
4.2	45	3.73
4.2	50	4.10
4.2	60	4.80
4.2	70	5.51
4.2	80	6.23
4.2	90	6.94
4.2	100	7.66
4.8	9.5	1.85

d	L	W
4.8	13	2.20
4.8	16	2.50
4.8	19	2.80
4.8	22	3.10
4.8	25	3.40
4.8	32	4.10
4.8	38	4.70
4.8	45	5.40
4.8	50	5.90
4.8	60	6.90
4.8	70	7.90
4.8	80	8.90
4.8	90	9.90
4.8	100	10.9
5.5	13	3.20
5.5	16	3.60
5.5	19	4.00
5.5	22	4.38
5.5	25	4.76
5.5	32	5.67
5.5	38	6.45
5.5	45	7.36
5.5	50	8.01
5.5	60	9.31
5.5	70	10.6
5.5	80	11.9

d	L	W
5.5	90	13.2
5.5	100	14.5
6.3	13	3.90
6.3	16	4.44
6.3	19	4.98
6.3	22	5.52
6.3	25	6.06
6.3	32	7.32
6.3	38	8.40
6.3	45	9.66
6.3	50	10.6
6.3	60	12.4
6.3	70	14.2
6.3	80	16.0
6.3	90	17.8
6.3	100	19.6

(W ~ Weights of standard sizes in kilograms per 1000 pieces)