


Socket Set Screws with Dog Point

Espárragos con punta de perro

Vis sans tête á six pans creux et tétón

| |
|----|
| A2 |
| A4 |



| d | M2 | M2.5 | M3 | M4 | M5 | M6 | M8 | M10 | M12 | M16 | M20 |
|----------------|------|------|------|------|-----|-----|------|------|------|-------|-------|
| d _p | 0.75 | 1.25 | 1.75 | 2.25 | 3.2 | 3.7 | 5.2 | 6.64 | 8.14 | 11.57 | 14.57 |
| t | 0.8 | 1.2 | 1.2 | 1.5 | 2 | 2 | 5 | 6 | 8 | 10 | 12 |
| s | 0.9 | 1.3 | 1.5 | 2 | 2.5 | 3 | 4 | 5 | 6 | 8 | 10 |
| pitch | 0.4 | 0.45 | 0.5 | 0.7 | 0.8 | 1 | 1.25 | 1.5 | 1.75 | 2 | 2.5 |

| d | L | W |
|------|----|------|
| M2 | 3 | .044 |
| M2 | 4 | .059 |
| M2 | 5 | .074 |
| M2 | 6 | .089 |
| M2 | 8 | .119 |
| M2 | 10 | .148 |
| M2 | 12 | .177 |
| M2.5 | 3 | .075 |
| M2.5 | 4 | .100 |
| M2.5 | 5 | .125 |
| M2.5 | 6 | .150 |
| M2.5 | 8 | .199 |
| M2.5 | 10 | .249 |
| M2.5 | 12 | .299 |
| M3 | 3 | .117 |
| M3 | 4 | .140 |
| M3 | 5 | .163 |
| M3 | 6 | .186 |
| M3 | 8 | .276 |
| M3 | 10 | .366 |
| M3 | 12 | .456 |
| M3 | 16 | .636 |
| M3 | 20 | .816 |
| M3 | 25 | 1.04 |
| M4 | 3 | .070 |
| M4 | 4 | .142 |
| M4 | 5 | .220 |

| d | L | W |
|----|----|------|
| M4 | 6 | .292 |
| M4 | 8 | .442 |
| M4 | 10 | .592 |
| M4 | 12 | .742 |
| M4 | 16 | 1.04 |
| M4 | 20 | 1.34 |
| M4 | 25 | 1.71 |
| M4 | 30 | 2.10 |
| M5 | 4 | .230 |
| M5 | 5 | .350 |
| M5 | 6 | .470 |
| M5 | 8 | .708 |
| M5 | 10 | .948 |
| M5 | 12 | 1.19 |
| M5 | 16 | 1.67 |
| M5 | 20 | 2.15 |
| M5 | 25 | 2.75 |
| M5 | 30 | 3.35 |
| M5 | 35 | 3.95 |
| M5 | 40 | 4.55 |
| M6 | 5 | .760 |
| M6 | 6 | .890 |
| M6 | 8 | 1.02 |
| M6 | 10 | 1.29 |
| M6 | 12 | 1.63 |
| M6 | 16 | 2.34 |
| M6 | 20 | 3.04 |

| d | L | W |
|-----|----|------|
| M 6 | 25 | 3.92 |
| M 6 | 30 | 4.80 |
| M 6 | 35 | 5.68 |
| M 6 | 40 | 6.60 |
| M 6 | 45 | 7.50 |
| M 6 | 50 | 8.40 |
| M 8 | 8 | 1.88 |
| M 8 | 10 | 2.28 |
| M 8 | 12 | 2.68 |
| M 8 | 16 | 3.94 |
| M 8 | 20 | 5.20 |
| M 8 | 25 | 6.79 |
| M 8 | 30 | 8.38 |
| M 8 | 35 | 9.97 |
| M 8 | 40 | 11.6 |
| M 8 | 45 | 13.2 |
| M 8 | 50 | 14.9 |
| M10 | 10 | 3.50 |
| M10 | 12 | 4.41 |
| M10 | 16 | 6.05 |
| M10 | 20 | 8.02 |
| M10 | 25 | 10.5 |
| M10 | 30 | 13.0 |
| M10 | 35 | 15.5 |
| M10 | 40 | 18.0 |
| M10 | 45 | 20.5 |
| M10 | 50 | 23.0 |

| d | L | W |
|-----|----|------|
| M10 | 60 | 28.0 |
| M12 | 12 | 6.82 |
| M12 | 16 | 8.91 |
| M12 | 20 | 11.0 |
| M12 | 25 | 14.6 |
| M12 | 30 | 18.2 |
| M12 | 35 | 21.8 |
| M12 | 40 | 25.4 |
| M12 | 45 | 29.0 |
| M12 | 50 | 32.6 |
| M12 | 60 | 39.8 |
| M16 | 12 | 12.1 |
| M16 | 16 | 16.1 |
| M16 | 20 | 20.1 |
| M16 | 25 | 25.1 |
| M16 | 30 | 31.9 |
| M16 | 35 | 38.2 |
| M16 | 40 | 44.9 |
| M16 | 45 | 50.9 |
| M16 | 50 | 56.5 |
| M16 | 60 | 67.5 |
| M20 | 20 | 28.6 |
| M20 | 25 | 38.9 |
| M20 | 30 | 45.5 |
| M20 | 35 | 55.8 |
| M20 | 40 | 66.1 |
| M20 | 45 | 76.4 |

| d | L | W |
|-----|----|------|
| M20 | 50 | 86.7 |
| M20 | 60 | 108 |

(W ~ Weights of standard sizes in kilograms per 1000 pieces)